


11.6" Multitouch Screen



Embedded 80 mm
Thermal Printer

HIPOPOS[®] lite

**Compact & high performance
ALL-IN-ONE POS**



Processor Quad-core
RK3566



Capacitive Screen
11.6"



Integrated Hard Disk
16 GB EMMC



RAM
2 GB DDR4

HIOPOS LITE	Technical specifications
Screen Size	11.6" HD Brightness : 220-250nits
Resolution	1366*768
Interface Type	EDP
Touchscreen	PCAP, Multitouch, USB
Motherboard	RK3566, Quad-core A55 CPU - 2.0Ghz
Ram	2Gb Ram -DDR4
EMMC	16Gb EMMC
Operating System	Android 11 with GMS
Dual Display Support	No
	Interfaces
LAN	100M
USB	2
HDMI	-
RS232	1
Micro USB	1
Audio	1
Cash Drawer	Extended from Printer
	Communication
Wi-Fi	2.4 & 5.0G
Bluetooth	4.2
Storage Temp	0 to 40oc Storage
Operating Temp	(-10oc – 50oc)
Power Adapter	24V, 2.5A
	POS Printer
Printer Type	Thermal Paper
Print Speed	170mm/sec
Mechanism type	CAPD347C Seiko Comptatible
Cutter	Partial Cut
Head	100Km
Cutter Life	500K
Cash Drawer	Extended to IO Panel